



ADVANTAGES

- Two burners
-
- Set of hyper-realistic logs
-
- Multi-program remote control
-
- Invisible safety screen
-
- Efficient heating
-
- Minimalist design
-
- Easy to use
-
- Energy saving



Size	B-60	B-80	B-100	B-100 H
Efficiency Energuide (NG LPG)	68.2% 65.2%	68.2% 65.2%	66.2% 67.2%	65.2% 66%
Maximum power (BTU)	1 burner 28 200 2 burners 47 000	1 burner 28 200 2 burners 47 000	1 burner 28 200 2 burners 47 000	1 burner 30 000 2 burners 50 000
Minimum power. (BTU)	1 burner 16 450 2 burners 28 200	1 burner 16 450 2 burners 28 200	1 burner 16 450 2 burners 28 200	1 burner 17 500 2 burners 30 000
Heating surface area	1 350 ft ²	1 350 ft ²	1 350 ft ²	1 450 ft ²
Weight	318 lb	315 lb	284 lb	435 lb
Direct vent	4/7	4/7	5/8	5/8
Valve and regulator	Maxitrol	Maxitrol	Maxitrol	Maxitrol
Convection system	standard	standard	standard	standard
A – Width*	42 ⁷ / ₁₆ "	50 ⁵ / ₁₆ "	58 ¹ / ₁₆ "	58 ¹ / ₁₆ "
B – Height	44"	39 ³ / ₄ "	27 ¹ / ₈ "	44 ⁷ / ₁₆ "
C – Depth*	21"	21"	20 ⁵ / ₁₆ "	21"
D – Opening width	23 ⁵ / ₈ "	31 ¹ / ₂ "	39 ¹ / ₄ "	39 ¹ / ₄ "
E – Opening height	31 ¹ / ₂ "	25 ⁷ / ₈ "	13 ⁹ / ₁₆ "	25 ⁷ / ₈ "
F – Chimney position*	10 ⁵ / ₈ "	10 ⁵ / ₈ "	9 ¹⁵ / ₁₆ "	10 ⁵ / ₈ "

* Dimensions including stand-off