


## ADVANTAGES

- Two burners
- 
- Set of hyper-realistic logs
- 
- Multi-program remote control
- 
- Invisible safety screen
- 
- Efficient heating
- 
- Minimalist design
- 
- Easy to use
- 
- Energy saving



| Size                            | B-60                                | B-80                                | B-100                               | B-100 H                             |
|---------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|
| Efficiency Energuide (NG   LPG) | 68.2%   65.2%                       | 68.2%   65.2%                       | 66.2%   67.2%                       | 65.2%   66%                         |
| Maximum power (BTU)             | 1 burner 28 200<br>2 burners 47 000 | 1 burner 28 200<br>2 burners 47 000 | 1 burner 28 200<br>2 burners 47 000 | 1 burner 30 000<br>2 burners 50 000 |
| Minimum power. (BTU)            | 1 burner 16 450<br>2 burners 28 200 | 1 burner 16 450<br>2 burners 28 200 | 1 burner 16 450<br>2 burners 28 200 | 1 burner 17 500<br>2 burners 30 000 |
| Heating surface area            | 1 350 ft <sup>2</sup>               | 1 350 ft <sup>2</sup>               | 1 350 ft <sup>2</sup>               | 1 450 ft <sup>2</sup>               |
| Weight                          | 318 lb                              | 315 lb                              | 284 lb                              | 435 lb                              |
| Direct vent                     | 4/7                                 | 4/7                                 | 5/8                                 | 5/8                                 |
| Valve and regulator             | Maxitrol                            | Maxitrol                            | Maxitrol                            | Maxitrol                            |
| Convection system               | standard                            | standard                            | standard                            | standard                            |
| A – Width*                      | 42 <sup>7</sup> / <sub>16</sub> "   | 50 <sup>5</sup> / <sub>16</sub> "   | 58 <sup>1</sup> / <sub>16</sub> "   | 58 <sup>1</sup> / <sub>16</sub> "   |
| B – Height                      | 44"                                 | 39 <sup>3</sup> / <sub>4</sub> "    | 27 <sup>1</sup> / <sub>8</sub> "    | 44 <sup>7</sup> / <sub>16</sub> "   |
| C – Depth*                      | 21"                                 | 21"                                 | 20 <sup>5</sup> / <sub>16</sub> "   | 21"                                 |
| D – Opening width               | 23 <sup>5</sup> / <sub>8</sub> "    | 31 <sup>1</sup> / <sub>2</sub> "    | 39 <sup>1</sup> / <sub>4</sub> "    | 39 <sup>1</sup> / <sub>4</sub> "    |
| E – Opening height              | 31 <sup>1</sup> / <sub>2</sub> "    | 25 <sup>7</sup> / <sub>8</sub> "    | 13 <sup>9</sup> / <sub>16</sub> "   | 25 <sup>7</sup> / <sub>8</sub> "    |
| F – Chimney position*           | 10 <sup>5</sup> / <sub>8</sub> "    | 10 <sup>5</sup> / <sub>8</sub> "    | 9 <sup>15</sup> / <sub>16</sub> "   | 10 <sup>5</sup> / <sub>8</sub> "    |

\* Dimensions including stand-off