



ADVANTAGES

- Two burners
-
- Set of hyper-realistic logs
-
- Multi-program remote control
-
- Invisible safety screen
-
- Efficient heating
-
- Minimalist design
-
- Easy to use
-
- Energy saving



| Size | B-60 | B-80 | B-100 | B-100 H |
|---------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|
| Efficiency Energuide (NG LPG) | 68.2% 65.2% | 68.2% 65.2% | 66.2% 67.2% | 65.2% 66% |
| Maximum power (BTU) | 1 burner 28 200 2 burners 47 000 | 1 burner 28 200 2 burners 47 000 | 1 burner 28 200 2 burners 47 000 | 1 burner 30 000 2 burners 50 000 |
| Minimum power. (BTU) | 1 burner 16 450 2 burners 28 200 | 1 burner 16 450 2 burners 28 200 | 1 burner 16 450 2 burners 28 200 | 1 burner 17 500 2 burners 30 000 |
| Heating surface area | 1 350 ft ² | 1 350 ft ² | 1 350 ft ² | 1 450 ft ² |
| Weight | 318 lb | 315 lb | 284 lb | 435 lb |
| Direct vent | 4/7 | 4/7 | 5/8 | 5/8 |
| Valve and regulator | Maxitrol | Maxitrol | Maxitrol | Maxitrol |
| Convection system | standard | standard | standard | standard |
| A - Width* | 42 ⁷ / ₁₆ " | 50 ⁵ / ₁₆ " | 58 ¹ / ₁₆ " | 58 ¹ / ₁₆ " |
| B - Height | 44" | 39 ³ / ₄ " | 27 ¹ / ₈ " | 44 ⁷ / ₁₆ " |
| C - Depth* | 21" | 21" | 20 ⁵ / ₁₆ " | 21" |
| D - Opening width | 23 ⁵ / ₈ " | 31 ¹ / ₂ " | 39 ¹ / ₄ " | 39 ¹ / ₄ " |
| E - Opening height | 31 ¹ / ₂ " | 25 ⁷ / ₈ " | 13 ⁹ / ₁₆ " | 25 ⁷ / ₈ " |
| F - Chimney position* | 10 ⁵ / ₈ " | 10 ⁵ / ₈ " | 9 ¹⁵ / ₁₆ " | 10 ⁵ / ₈ " |

* Dimensions including stand-off