



ADVANTAGES


- Heating power adapted to the smallest spaces
-
- Precision assembly
-
- Automatic combustion air inlet calibration
-
- Produces little ash
-
- Easy to light
-
- Fits all masonry hearths
-
- Energy-efficient performance



● 66x50



● 76x55



● 76x60


Size	● 66x50	● 76x55	● 76x60
Maximum length of logs	16"	20"	20"
Efficiency (EPA)	68,4%	67,6%	68,3%
Particle emissions	1,93 g/h	1,86 g/h	1,89 g/h
Maximum power*	49 000 BTU/h	58 000 BTU/h	64 000 BTU/h
EPA power*	17 121 BTU/h	21 732 BTU/h	23 388 BTU/h
Nominal heat output*	34 000 BTU/h	39 000 BTU/h	44 000 BTU/h
Heating surface area	1 000 pi ²	1 300 pi ²	1 400 pi ²
Firebox size	1.08 pi ³	1.55 pi ³	1.58 pi ³
Glass width	20 9/16"	24 1/2"	24 1/2"
Glass height	12 1/16"	14 1/16"	16"
Outside air duct	ø 4"	ø 4"	ø 4"
Weight	165 lb	190 lb	200 lb

*For additional information on powers, please see: <https://stuvamerica.com/en/inspirations/tips-and-techniques/power-btu/>
 Dimensions for information only. See the installation manuals for details.


FINISHING FRAMES

REQUIRED ACCESSORY


Choose from the following options:



66X50




76X55




76X60

THIN EDGE




Width	26"	29 ¹⁵ / ₁₆ "	29 ¹⁵ / ₁₆ "
Height	19 ¹¹ / ₁₆ "	21 ¹¹ / ₁₆ "	23 ⁵ / ₈ "

PICTURE TYPE 2"



Width	29 ³ / ₈ "	33 ⁵ / ₁₆ "	33 ⁵ / ₁₆ "
Height	21 ³ / ₈ "	23 ³ / ₈ "	25 ⁵ / ₁₆ "

PICTURE TYPE 4"



Width	33 ⁵ / ₁₆ "	37 ¹ / ₄ "	37 ¹ / ₄ "
Height	23 ³ / ₈ "	25 ⁵ / ₁₆ "	27 ⁵ / ₁₆ "

PICTURE TYPE 6"



Width	37 ¹ / ₄ "	41 ³ / ₁₆ "	41 ³ / ₁₆ "
Height	25 ⁵ / ₁₆ "	27 ⁵ / ₁₆ "	29 ¹ / ₄ "

Dimensions for information only. See the installation manuals for details.

AVAILABLE COLOR



Matte black – STOVE BRIGHT 6304