

StuvGrey ●
Black ●


To ensure dimensions, performance data and other prerequisites for a safe installation are in compliance with current regulations, always refer to the installation instructions available on the website www.stuvamerica.com.

Product


58



68



78



Performances

| | | | |
|---------------------------|--------------------------------|--------------------------------|--------------------------------|
| Particulate matter | 1.5 g/h | 1.7 g/h | 1.8 g/h |
| Burn rate | 4.1 lb/h | 4.1 lb/h | 4.4 lb/h |
| EPA Efficiency | 71 % | 66 % | 67 % |
| Maximum heat output | 65 000 BTU/h | 82 000 BTU/h | 86 000 BTU/h |
| EPA heat output | 27 015 BTU/h | 23 727 BTU/h | 27 092 BTU/h |
| Nominal heat output | 46 000 BTU/h | 50 000 BTU/h | 58 000 BTU/h |
| Certifications | UL / ULC / EPA / CSA B415.1-22 | UL / ULC / EPA / CSA B415.1-22 | UL / ULC / EPA / CSA B415.1-22 |
| Combustion chamber volume | 1.6 ft ³ | 1.9 ft ³ | 2.2 ft ³ |
| Logs - Maximum length | 17" | 21" | 25" |
| Estimated heating area | 1 400 ft ² | 1 650 ft ² | 2 100 ft ² |
| Weight | 332 lb | 362 lb | 396 lb |

Dimensions

| | | | |
|---------------------------------|----------|----------|----------|
| [A] Width | 22 7/8" | 26 3/4" | 30 3/4" |
| [B] Depth | 18" | 18" | 18" |
| [C] Height | 39 3/4" | 39 3/4" | 39 3/4" |
| [D] Center chimney - side | 11 7/16" | 13 3/8" | 15 3/8" |
| [E] Center chimney - back | 5 1/8" | 5 1/8" | 5 1/8" |
| [F] Chimney diameter | 6" or 7" | 6" or 7" | 6" or 7" |
| [H] Min. ceiling clearance | 24 1/2" | 24 1/2" | 24 1/2" |
| [J] Min. back clearance | 7" | 7" | 7" |
| [K] Log storage height | 15 3/4" | 15 3/4" | 15 3/4" |
| [L1] Min. side clearance | 12" | 12" | 12" |
| [L2] Recess min. side clearance | 15" | 15" | 15" |
| Ø Outside air connection | 4" | 4" | 4" |
| Glass width | 17 5/8" | 21 5/8" | 25 1/2" |
| Glass height | 16 9/16" | 16 9/16" | 16 9/16" |