

Product	58	68	78

Performances

Particulate matter	1.5 g/h	1.7 g/h	1.8 g/h
Burn rate	4.1 lb/h	4.1 lb/h	4.4 lb/h
EPA Efficiency	71 %	66 %	67 %
Maximum heat output	65 000 BTU/h	82 000 BTU/h	86 000 BTU/h
EPA heat output	27 015 BTU/h	23 727 BTU/h	27 092 BTU/h
Nominal heat output	46 000 BTU/h	50 000 BTU/h	58 000 BTU/h

Certifications	UL / ULC / EPA / CSA B415.1-22	UL / ULC / EPA / CSA B415.1-22	UL / ULC / EPA / CSA B415.1-22
----------------	--------------------------------	--------------------------------	--------------------------------

Combustion chamber volume	1.6 ft ³	1.9 ft ³	2.2 ft ³
Logs - Maximum length	17"	21"	25"
Estimated heating area	1 400 ft ²	1 650 ft ²	2 100 ft ²
Weight	180 lb	205 lb	228 lb

Dimensions

[A] Width	22 7/8"	26 3/4"	30 3/4"
[B] Depth	17 5/16"	17 5/16"	17 5/16"
[C] Height	23 7/8"	23 7/8"	23 7/8"
[D] Center chimney - side	11 7/16"	13 3/8"	15 3/8"
[E] Center chimney - back	4 7/16"	4 7/16"	4 7/16"
[F] Chimney diameter	6" or 7"	6" or 7"	6" or 7"
Ø Outside air connection	4"	4"	4"
Glass width	17 5/8"	21 5/8"	25 1/2"
Glass height	16 7/16"	16 7/16"	16 7/16"



Frames

58

68

78

Thin-edge frame


contour 1/8"



W	22 7/8"	26 3/4"	30 3/4"
H	23 7/8"	23 7/8"	23 7/8"
Color	StüvGrey ●		

Picture-type frame


contour 2"



W	26 5/8"	30 5/16"	34 1/4"
H	25 1/2"	25 1/2"	25 1/2"
Color	StüvGrey ●		

Picture-type frame


contour 4"



W	30 5/16"	34 1/4"	38 3/16"
H	27 7/16"	27 7/16"	27 7/16"
Color	StüvGrey ●		

Picture-type frame


contour 6"



W	34 1/4"	38 3/16"	42 1/8"
H	29 7/16"	29 7/16"	29 7/16"
Color	StüvGrey ●		

Custom frame

3-sided



L	variable	variable	variable
H	variable	variable	variable
Color	StüvGrey ●		